

## Low Profile Ultra High Intensity Curve Shape LED light Bar

### Specification:


Ultra high intensity LED. features a sealed, water-resistant (rate IP67), PC<sup>+</sup> lens, aluminum alloy housing. Design for off road & working truck driving & area lighting.

Operating Voltage: 12V-24V DC (10-30Volts)

Operating Temperature-40C°- 85C°

Beam Type: Spot beam 30°, flood beam 60°

Order Number:	L	Beam	Watts	Lumen Output	D	Ht	H	W	W (mounting size)
W2413500:	13"	Spot	72 W	5040	3.56"/90.5mm	4.72"/120mm	2.97"/75.5mm	14.21"/361mm	1 5.67"/398mm
W2413510:	13	Flood	72 W	5040	3.56"/90.5mm	4.72"/120mm	2.97"/75.5mm	14.21"/361mm	1 5.67"/398mm
W4022580:	22"	Combo	120 W	7900	3.84"/97.5mm	4.72"/120mm	2.97"/75.5mm	22.32"/567mm	23.74"/603mm
W6033580:	33"	Combo	180 W	11450	4.37"/111mm	4.72"/120mm	2.97"/75.5mm	32.41"/823.3mm	33.8"/858.4mm
W8042580:	42"	Combo	240 W	16500	5.12"/130mm	4.72"/120mm	2.97"/75.5mm	42.40"/1077mm	43.7"/1110mm
W9650580:	50"	Combo	288 W	19200	5.87"/149mm	4.72"/120mm	2.97"/75.5mm	47.56"/1208mm	51.67"/1312.5mm



\*\*Listed maximum lumen output is based on individual LED lab test results. Actual lumen output may vary.



24853 AVE ROCKEFELLER, VALENCIA CA 91355 WWW.ALT-ENT.COM  
SALES@ALT-ENT.COM TEL:(661)705-5727, FAX:(661)294-9183