

4" Round and 6" Oval Emergency Warning Light

4" Round LED light that functions as a EMERGENCY WARNING light for DOT work truck, emergency vehicle. U.S. independent laboratory tested meets or exceeds latest DOT FMVSS 108 and SAE standards, SAE J595, J1318 class 1 approved for primary emergency warning light use.

Specifications

Features a sealed, water-resistant, polycarbonate optical lens and housing. Internal built in 5X flashing pattern, alternating flashing controller.

(operate with 1X CA title 13, 4X flashing pattern, freedom, alternating and simultaneous flashing controller are available as option for OEM larges quantity purchase)

Operating Voltage: 12V-24V DC (8-32V)

Operating Current: <2.0 A (tested at 12.8V)

Order Number:

F1912101: 12V-24V DC, Amber LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1912201: 12V-24V DC, Blue LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1912301: 12V-24V DC, Red LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1912501: 12V-24V DC, White LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness


Order Number:

F1914101: 12V-24V DC, Amber LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1914201: 12V-24V DC, Blue LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1914301: 12V-24V DC, Red LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness

F1914501: 12V-24V DC, White LED, 5X Flashing Pattern, Alternating Flashing Controller, PVC Grommet. Weather-Pak Connector Harness



5" Round / PAR46 Emergency Warning Light

5" Round LED light that functions as a EMERGENCY WARNING light for DOT work truck, emergency vehicle. U.S. independent laboratory tested meets or exceeds latest DOT FMVSS 108 and SAE standards, SAE J595, CA title 13 approved for primary emergency warning light use.

Specifications

Features a sealed, water-resistant, polycarbonate optical lens and housing. Internal built in 1X CA title 13 flashing pattern, alternating flashing controller. Light head fit in regular PAR46 housing.

Operating Voltage: 12V-24V DC (8-32V)

Operating Current: <2.5 A (tested at 12.8V)

Order Number:


F3502140: 12V-24V DC, Amber LED, 1X CA Title 13 Flashing Pattern, Weather-Pak Connector Harness

F3502141: 12V-24V DC, Amber LED, 1X CA Title 13 Flashing Pattern, PVC Grommet. Weather-Pak Connector Harness

F3502142: 12V-24V DC, Amber LED, 1X CA Title 13 Flashing Pattern, Rubber Tractor Bowl. Weather-Pak Connector Harness

F3510001: PVC Grommet

F3510002: Rubber Tractor Bowl



27636 AVE SCOTT STE D, VALENCIA CA 91355 WWW.ALT-ENT.COM

SALES@ALT-ENT.COM TEL: (661)295-6818, FAX: (661)295-6816

TOLL FREE: TEL: (844)406-6818 FAX: (844)881-6816, EFAX:(888)774-9793